


Features & Applications

The PDX-6 Down LED uses High Intensity Cree LED as its light source. It comes with an aluminium/acrylic fixture with spring clips for easy installation. Each lamp comes complete with an external driver. They are ideal for boutiques, lobbies, lifts, etc. They can be easily applied in ceilings, cabinets or under counters.

Dimensions

Cut-out Diameter: 72 mm



Product Specifications

Light Source	3x 1W High Power CREE LED
Driver Type	External Constant Current Driver
Driver Power Input	100~240Vac; 50~60 Hz
Power Consumption	Max 3.6W (lamp only)
Lumen per Lamp	Min 240 lm (Day Light)
Intensity per Lamp @ 1m	1,050 lux (Day Light) on 30 Deg Lens
Lens Options	Standard: 30 deg. Custom: 60 deg
Colour Options	Standard: Day Light (Typ 6000K), Warm White (Typ 3000K) Custom: Red, Green, Blue, Amber
Operating Temperature	-5 ~ +40 deg C
Estimated Lamp Life	50,000 Hrs

Models

PDX-631YY

YY	2 digits depict lens angle (deg)	30, 60. Standard: 30
X	Alphabet depicts LED colour	B : Day Light, E : Warm White, R : Red, G : Green, L : Blue, Y : Amber
Standard Models: PDB-63130, PDE-63130. MOQ applies for other models		

Prime Light Pte Ltd reserves the right to change the specification without prior notification.